



# MATERIAL SAFETY DATA SHEET

---

---

## Section 1: Product & Company Identification

---

---

**Product Name:** Diesel Fuel Anti-Gel  
**Product Number (s):** 75221  
**Product Use:** diesel fuel additive for cold weather

### Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.  
885 Louis Drive  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)  
1-215-674-4300(General)  
(800) 521-3168 (Technical)  
(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.  
2-1246 Lorimar Drive  
Mississauga, Ontario L5S 1R2  
[www.crc-canada.ca](http://www.crc-canada.ca)  
1-905-670-2291

In Mexico:

CRC Industries Mexico  
Av. Benito Juárez 4055 G  
Colonia Orquídea  
San Luís Potosí, SLP CP 78394  
[www.crc-mexico.com](http://www.crc-mexico.com)  
52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

---

---

## Section 2: Hazards Identification

---

---

### Emergency Overview

**DANGER:** Flammable. Harmful or Fatal if Swallowed. Vapor Harmful.  
As defined by OSHA's Hazard Communication Standard, this product is hazardous.  
Appearance & Odor: Dark amber liquid, petroleum odor

### Potential Health Effects:

**ACUTE EFFECTS:**

**EYE:** May cause mild eye irritation. Symptoms include stinging, tearing and redness.

**SKIN:** Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of the skin, burns and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during normal use.

**INHALATION:** Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms include irritation of the nose, throat and airways and tightening of chest. Extended exposure may lead to central nervous system depression, including dizziness, drowsiness, weakness, fatigue, nausea, headache and unconsciousness.

**INGESTION:** Ingestion may cause gastrointestinal disturbance, including irritation, nausea, vomiting and diarrhea. The major health threat of ingestions occurs from the danger of aspiration of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage and even death.

**CHRONIC EFFECTS:** Prolonged or repeated exposure to vapors may lead to central nervous system effects, and effects on memory. Components of this product have been shown to cause cancer in laboratory animals, but the relevance of this finding to humans is uncertain.

**TARGET ORGANS:** Central nervous system; possibly liver, kidney, testis, hearing

**Product Name: Diesel Fuel Anti-Gel**

**Product Number (s): 75221**

Medical Conditions Aggravated by Exposure: pre-existing skin or lung conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

---

---

### Section 3: Composition/Information on Ingredients

---

---

COMPONENT	CAS NUMBER	% by Wt.
Xylene	1330-20-7	50 - 60
Petroleum naphtha	64742-94-5	20 - 30
Ethylbenzene	100-41-4	10 - 15
Tall oil fatty acid	61790-12-3	2 - 5
Naphthalene	91-20-3	2.2

---

---

### Section 4: First Aid Measures

---

---

**Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Wash contaminated clothing prior to re-use.

**Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

**Ingestion:** Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean forward to reduce the risk of aspiration. Monitor for breathing difficulties. Mouth can be rinsed to dissipate the taste.

**Note to Physicians:** Inhalation of high concentrations of this material may be associated with cardiac arrhythmias. Sympathomimetic drugs initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

---

---

### Section 5: Fire-Fighting Measures

---

---

**Flammable Properties:** As defined by OSHA, this product is a Class IC Flammable Liquid.  
Flash Point: 87°F / 31°C (TCC) Upper Explosive Limit: 6.6  
Autoignition Temperature: > 900°F / 482°C Lower Explosive Limit: 1.0

**Fire and Explosion Data:**

**Suitable Extinguishing Media:** Use extinguishers rated for Class B fires, such as dry chemical, Halon, fire fighting foam or CO<sub>2</sub>.

**Products of Combustion:** Oxides of carbon

**Explosion Hazards:** Containers, when exposed to heat from fire, may build pressure and rupture. Vapors may accumulate in a confined space and create a flammable atmosphere.

**Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

**Product Name: Diesel Fuel Anti-Gel**

**Product Number (s): 75221**

and to knock down vapors which may result from product decomposition.

---

---

## Section 6: Accidental Release Measures

---

---

**Personal Precautions:** Use personal protection recommended in Section 8.

**Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

**Methods for Containment & Clean-up:** Remove all sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

---

---

## Section 7: Handling and Storage

---

---

**Handling Procedures:** Keep away from heat, sparks, and open flame. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion. Provide adequate ventilation during use. Do not breathe vapors. Wash hands after use. For product use instructions, please see the product label.

**Storage Procedures:** Store in a cool dry area out of direct sunlight. Containers should be tightly closed while in storage. Store in a well ventilated area. Keep out of reach of children.

**Aerosol Storage Level:** NA

---

---

## Section 8: Exposure Controls/Personal Protection

---

---

### **Exposure Guidelines:**

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Xylene	100	150 (v)	100	150	NE		ppm
Petroleum naphtha	NE	NE	NE	NE	NE		
Ethylbenzene	100	125 (v)	100	125	NE		ppm
Tall oil fatty acid	NE	NE	NE	NE	NE		
Naphthalene	10	15(v)	10 (s)	15	NE		ppm
N.E. – Not Established      (c) – ceiling      (s) – skin      (v) – vacated							

### **Controls and Protection:**

**Engineering Controls:** Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

**Respiratory Protection:** None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

**Product Name: Diesel Fuel Anti-Gel**

**Product Number (s): 75221**

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, neoprene or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

---

## Section 9: Physical and Chemical Properties

---

---

Physical State: liquid

Color: amber

Odor: petroleum

Odor Threshold: ND

Specific Gravity: 0.880

Initial Boiling Point: > 250°F

Freezing Point: ND

Vapor Pressure: ~ 9 mmHg @ 68°F

Vapor Density: > 1 (air = 1)

Evaporation Rate: slow

Solubility: negligible in water

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 96.4                      g/L: 848.3                      lbs./gal: 7.1

---

---

## Section 10: Stability and Reactivity

---

---

Stability: Stable

Conditions to Avoid: Temperature extremes, sources of ignition

Incompatible Materials: Strong oxidizers

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, various hydrocarbons

Possibility of Hazardous Reactions: No

---

---

## Section 11: Toxicological Information

---

---

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

### Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Xylene	4300 mg/kg	> 1700 mg/kg	5000 ppm/4H
Petroleum naphtha	No data	> 2 mL/kg	> 590 mg/m <sup>3</sup> /4H
Ethylbenzene	3500 mg/kg	> 5000 mg/kg	55,000 mg/m <sup>3</sup> /2H
Tall oil fatty acid	> 5000 mg/kg	> 2000 mg/kg	No data
Naphthalene	490 mg/kg	> 20 g/kg	No data

**Product Name: Diesel Fuel Anti-Gel**

**Product Number (s): 75221**

**Chronic Toxicity:**

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Xylene	No	No	No	E (mild) / S (moderate)	Unknown
Petroleum naphtha	No	No	No	E (mild) / S (moderate)	Unknown
Ethylbenzene	No	Group 2B	No	E (moderate) / S (mild)	Unknown
Tall oil fatty acid	No	No	No	No	No
Naphthalene	No	Group 2B	Reasonably Anticipated to be a Carcinogen	E (moderate) / S (mild) / R (moderate)	Unknown

E – Eye      S – Skin      R - Respiratory

Reproductive Toxicity: No information available  
Teratogenicity: No information available  
Mutagenicity: No information available  
Synergistic Effects: No information available

---

---

**Section 12: Ecological Information**

---

---

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Ethylbenzene -- 48 Hr EC50 Daphnia magna: 1.8-2.4 mg/L  
Naphthalene -- 48 Hr EC50 water flea: 2.16 mg/L  
Persistence / Degradability: No information available  
Bioaccumulation / Accumulation: No information available  
Mobility in Environment: No information available

---

---

**Section 13: Disposal Considerations**

---

---

**Waste Classification:** This product is a RCRA hazardous waste for the flammability characteristic and the toxicity characteristic (18.5 mg/L Benzene) with the following waste codes: D001, D018. (See 40 CFR Part 261.20 – 261.33) Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

---

---

**Section 14: Transport Information**

---

---

US DOT (ground): Consumer Commodity, ORM-D  
ICAO/IATA (air): Flammable liquids, N.O.S. (Xylene, Petroleum naphtha), UN1993, 3, PGIII, Limited Quantity  
IMO/IMDG (water): Flammable liquids, N.O.S. (Xylene, Petroleum naphtha), UN1993, 3, PGIII, Limited Quantity  
Special Provisions: None

**Product Name: Diesel Fuel Anti-Gel**

**Product Number (s): 75221**

---

---

## **Section 15: Regulatory Information**

---

---

### **U.S. Federal Regulations:**

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Xylene (100 lbs)  
Ethylbenzene (1000 lbs)  
Naphthalene (100 lbs)

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:

Fire Hazard	Yes
Reactive Hazard	No
Release of Pressure	No
Acute Health Hazard	Yes
Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

Xylene (53%), Ethylbenzene (13.2%), Naphthalene (2.2%)

#### Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Xylene, Ethylbenzene, Naphthalene

### **U.S. State Regulations:**

#### California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

Ethylbenzene (13.2%)  
Naphthalene (2.2%),  
Benzene (0.002%)

Consumer Products VOC Regulations: This product is not regulated.

#### State Right to Know:

New Jersey: 91-20-3, 800967-5503P, 800967-5453P, 1330-20-7, 100-41-4  
Pennsylvania: 91-20-3, 1330-20-7, 100-41-4  
Massachusetts: 91-20-3, 1330-20-7, 100-41-4  
Rhode Island : 91-20-3, 1330-20-7, 100-41-4

### **Canadian Regulations:**

#### Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: B2, D1B, D2A

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

**Product Name: Diesel Fuel Anti-Gel**  
**Product Number (s): 75221**

---

**European Union Regulations:**

**RoHS Compliance:** This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

**Additional Regulatory Information:** This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

---


---

**Section 16: Other Information**

---

---

HMIS® (II)	
Health:	2
Flammability:	3
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick  
CRC #: 929  
Revision Date: 03/30/2010

Changes since last revision: Section 3: Compositional change

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists  
CAS: Chemical Abstract Service  
CFR: Code of Federal Regulations  
DOT: Department of Transportation  
DSL: Domestic Substance List  
g/L: grams per Liter  
HMIS: Hazardous Materials Identification System  
IARC: International Agency for Research on Cancer  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
IMDG: International Maritime Dangerous Goods  
IMO: International Maritime Organization  
lbs./gal: pounds per gallon  
LC: Lethal Concentration  
LD: Lethal Dose

NA: Not Applicable  
ND: Not Determined  
NIOSH: National Institute of Occupational Safety & Health  
NFPA: National Fire Protection Association  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration  
PMCC: Pensky-Martens Closed Cup  
PPE: Personal Protection Equipment  
ppm: Parts per Million  
RoHS: Restriction of Hazardous Substances  
STEL: Short Term Exposure Limit  
TCC: Tag Closed Cup  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Information System