

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version 5.3      Revision Date: 05/30/2022      SDS Number: 10766012-00008      Date of last issue: 09/21/2021  
Date of first issue: 02/07/2017

---

**SECTION 1. IDENTIFICATION**

Product name : ROST OFF GOLD, Foaming rust releaser, 215 g  
Product code : 890.20011  
Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited  
Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1  
Telephone : +1 (905) 564 6225  
Telefax : +1 (905) 564 3671  
Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:  
CHEMTREC (24/7): 1-800-424-9300  
Transport related emergencies:  
CANUTEC (24/7): 1-613-996-6666 or \* 666 (cell)  
  
Urgences impliquant un déversement, incendie, explosion ou exposition:  
CHEMTREC (24/7): 1-800-424-9300  
Urgences liées au transport:  
CANUTEC (24/7): 1-613-996-6666 ou \* 666 (cellulaire)  
  
E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Lubricant  
  
Restrictions on use : Not applicable

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Skin sensitization : Category 1  
Specific target organ toxicity : Category 3  
- single exposure

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version 5.3      Revision Date: 05/30/2022      SDS Number: 10766012-00008      Date of last issue: 09/21/2021  
Date of first issue: 02/07/2017

---

Eye irritation : Category 2A

Skin irritation : Category 2

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, eye protection and face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P337 + P313 If eye irritation persists: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to tempera-

# ROST OFF GOLD, Foaming rust releaser, 215 g

Version 5.3      Revision Date: 05/30/2022      SDS Number: 10766012-00008      Date of last issue: 09/21/2021  
Date of first issue: 02/07/2017

tures exceeding 50 °C (122 °F).

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

**Components**

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Butane	No data available	106-97-8	>= 30 - < 60 *
Propane	Dimethylmethane	74-98-6	>= 10 - < 30 *
Distillates (petroleum), hydrotreated light	C13-14 ALKANE	64742-47-8	>= 10 - < 30 *
Amides, tall-oil fatty, N,N-bis(hydroxyethyl)	Tall oil diethanolamide	68155-20-4	>= 1 - < 5 *
Zinc naphthenate	Naphthenic acids, zinc salts	12001-85-3	>= 0.1 - < 1 *

\* Actual concentration or concentration range is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.

## ROST OFF GOLD, Foaming rust releaser, 215 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

- Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Flash back possible over considerable distance.  
Vapors may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.

**ROST OFF GOLD, Foaming rust releaser, 215**
**g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

- Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.
- Conditions for safe storage : Store locked up.  
Keep tightly closed.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.

**ROST OFF GOLD, Foaming rust releaser, 215  
g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable solids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Substances and mixtures which in contact with water emit flammable gases  
 Explosives  
 Gases

Recommended storage temperature : < 35 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
		TWA	525 mg/m <sup>3</sup>	CA ON OEL

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

**Personal protective equipment**

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Self-contained breathing apparatus
- Hand protection
- Material : Nitrile rubber
- Glove thickness : 0.4 mm
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Eye protection : Wear the following personal protective equipment:  
Safety goggles
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : Aerosol containing a liquefied gas
- Propellant : Butane, Propane
- Color : light yellow
- Odor : characteristic

**ROST OFF GOLD, Foaming rust releaser, 215  
g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Density	:	0.83 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
------------	---	--



**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapors may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**Distillates (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Mouse): > 0.219 mg/l  
Exposure time: 3 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Remarks: Based on data from similar materials

**Zinc naphthenate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Distillates (petroleum), hydrotreated light:**

Species : Rabbit  
Result : Skin irritation

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Zinc naphthenate:**

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439

Result : No skin irritation

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Distillates (petroleum), hydrotreated light:**

Species : Rabbit  
Result : No eye irritation

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Species : Rabbit  
Result : Irreversible effects on the eye  
Remarks : Based on data from similar materials

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version 5.3      Revision Date: 05/30/2022      SDS Number: 10766012-00008      Date of last issue: 09/21/2021  
Date of first issue: 02/07/2017

---

**Zinc naphthenate:**

Species : Bovine cornea  
Method : OECD Test Guideline 437

Species : Tissue Culture  
Method : OECD Test Guideline 492

Result : Irritation to eyes, reversing within 21 days

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated light:**

Test Type : Buehler Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative  
Remarks : Based on data from similar materials

**Zinc naphthenate:**

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Result : positive  
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**ROST OFF GOLD, Foaming rust releaser, 215  
g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

**Distillates (petroleum), hydrotreated light:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Intraperitoneal injection  
Result: negative

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Mouse  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

**Zinc naphthenate:**

**ROST OFF GOLD, Foaming rust releaser, 215****g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated light:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 105 weeks  
Result : negative

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Species : Rat  
Application Route : Skin contact  
Exposure time : 104 weeks  
Result : negative  
Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version 5.3      Revision Date: 05/30/2022      SDS Number: 10766012-00008      Date of last issue: 09/21/2021  
Date of first issue: 02/07/2017

---

Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Distillates (petroleum), hydrotreated light:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Skin contact  
Method: OECD Test Guideline 421  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Skin contact  
Method: OECD Test Guideline 421  
Result: negative

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Butane:**

Assessment : May cause drowsiness or dizziness.

**Propane:**

Assessment : May cause drowsiness or dizziness.

**Distillates (petroleum), hydrotreated light:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Butane:**

Species : Rat  
NOAEL : 9000 ppm

**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Propane:**

Species : Rat  
NOAEL : 7.214 mg/l  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Distillates (petroleum), hydrotreated light:**

Species : Rat  
NOAEL : >= 750 mg/kg  
Application Route : Ingestion  
Exposure time : 21 Weeks

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Species : Rat  
NOAEL : > 100 mg/kg  
Application Route : Skin contact  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

**Aspiration toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated light:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Distillates (petroleum), hydrotreated light:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 1.4 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

**ROST OFF GOLD, Foaming rust releaser, 215  
g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 3 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 0.48 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1 - 10 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50: > 1 - 10 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOELR: > 0.1 - 1 mg/l  
Exposure time: 28 d  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): > 0.01 - 0.1 mg/l  
Exposure time: 21 d  
Remarks: Based on data from similar materials

**Zinc naphthenate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.1 - 1 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC (activated sludge): 0.1 mg/l  
Exposure time: 4 h  
Remarks: Based on data from similar materials

**Persistence and degradability****Components:****Butane:**



**ROST OFF GOLD, Foaming rust releaser, 215 g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

**Biodegradability** : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Propane:**

**Biodegradability** : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated light:**

**Biodegradability** : Result: Not readily biodegradable.  
Biodegradation: 58.6 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

**Biodegradability** : Result: Readily biodegradable.  
Remarks: Based on data from similar materials

**Zinc naphthenate:**

**Biodegradability** : Result: Not readily biodegradable.  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Butane:**

Partition coefficient: n-  
octanol/water : log Pow: 2.31

**Distillates (petroleum), hydrotreated light:**

Partition coefficient: n-  
octanol/water : log Pow: > 4  
Remarks: Based on data from similar materials

**Amides, tall-oil fatty, N,N-bis(hydroxyethyl):**

Partition coefficient: n-  
octanol/water : log Pow: > 4  
Remarks: Expert judgment

**Zinc naphthenate:**

Partition coefficient: n-  
octanol/water : log Pow: > 4  
Remarks: Expert judgment

**Mobility in soil**

No data available

# ROST OFF GOLD, Foaming rust releaser, 215 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

- UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

#### IATA-DGR

- UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

#### IMDG-Code

- UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# ROST OFF GOLD, Foaming rust releaser, 215 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

## Domestic regulation

### TDG

UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### The ingredients of this product are reported in the following inventories:

DSL	:	All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
-----	---	--

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA ON OEL	:	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA ON OEL / TWA	:	Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

**ROST OFF GOLD, Foaming rust releaser, 215****g**

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
5.3	05/30/2022	10766012-00008	Date of first issue: 02/07/2017

---

tem; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/30/2022  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8